

- according to one of the Claims 1 or 2, **characterized by the fact** that the textile curtain (15) is formed, which is fastened on one end over almost the entire width of recess (9) beneath the rear edge (11) of recess (9) and is held, on the other hand, on an area of the roof (3) where, over at least part of its extent it forms a surface (22) that is essentially horizontal, and is positioned elevated relative to its connection (21) to body (4).
4. Cabriolet vehicle (1) according to one of the Claims 2 or 3, **characterized by the fact** that a fastening device (23) for lining (15) is formed by the molded part in an area behind the support step (16).
 5. Cabriolet vehicle (1) according to one of the Claims 1 to 4, **characterized by the fact** that the lining (15) visually covers the gap (14) on the top between the edge (11) of auto body (4) and the opened roof (3).
 6. Cabriolet vehicle (1) according to one of the Claims 1 to 5, **characterized by the fact** that the edge (11) of auto body (4) overall has a curved trend, which includes the areas (11a) running forward to the vehicle sides in the direction of travel.
 7. Cabriolet vehicle (1) according to Claim 6, **characterized by the fact** that the edge (11) at least in parts of its area is the front edge of a trunk lid (13).
 8. Cabriolet vehicle (1) according to one of the Claims 1 to 6, **characterized by the fact** that the edge (11) at least in parts of its area is the front edge of a cross bar (25) of the body outer surface (24) arranged in front of a trunk lid (13).